

If you're serious about

Material Handling

get serious about

Magnets.



Eagle Lift Magnets

Alpha Eagle Lift Offers:

- **Permanent Magnet**; does NOT require electricity
- Smooth Lever Action between Off & On positions
- Bi-Polar capabilities enable the unit to lift both **flat and round stock** safely
- Unique "Test Talon" safety feature allows the operator to undertake a trial lift on questionable loads
- Safety factors exceeding industry standards
- Single hand operation
- Very little residual magnetism at OFF makes lifter positioning easier
- **Custom Pole shoes** can be designed for special applications
- In-house test facility
- Portable, compact and lightweight
- 3 Year Warranty
- **Made in the USA**

Product Specifications (Imperial Data)

Model Number	Safe Working Load (SWL)*		Product Dimensions					
	Flat Capacity (lbs)	Round Capacity (lbs/range inch)	Min Load Thickness (in)	Max Load Length (ft)	Unit Weight (lbs)	L (in)	W (in)	H (in)
EL-250	250	N/A	1	4	10	4 ½	5	4 ½
EL-600	600	300/4-12	1	6	16	6 ½	5	4 ½
EL-1200	1200	600/4-12	1	10	30	10 ½	5	4 ½
EL-2500	2500	1250/6-20	1.37	10	115	14 ½	7 ½	7 ½
EL-5000	5000	2500/6-20	1.37	12	210	25 ½	7 ½	7 ½

Test load is approximately three times rated load.

Variation on round capacities are available as a special order.

*Never exceed SWL (Safe Working Load) and always observe safe lifting practices.

The Pole/Workpiece contact area is absolute minimum permissible.

Test load was based on a machined, flat, mild steel of greater than or equal to the minimum thickness stated.



ALPHA

WORKHOLDING SOLUTIONS

127 Advantage Place

Statesville, NC 28677

(704) 871.2183 • (704) 871.2184 Fax

1.877.217.6900 Toll Free

www.alphaworkholding.com